

Current Draw and Thermal Dissipation RAM Audio DALIM Series

230V AC

Model	1/8 Power PN															
	Idle				8 ohm				4 ohm				2 ohm			
	BTU/h	kCal/h	W line	A line	BTU/h	kCal/h	W line	A line	BTU/h	kCal/h	W line	A line	BTU/h	kCal/h	W line	A line
DALIM-5Q	290,03	73	85	0,7	655	165	817	3,7	655	165	817	3,7	655	165	817	3,7
DALIM-10Q	290,03	73	85	0,7	655	165	817	3,7	1310	330	1634	7,3	1310	330	1634	7,3
DALIM-14Q	382	96	112	1,0	943	238	1176	5,4	1834	462	2288	10,0	1834	462	2288	10,0
DALIM-20Q	382	96	112	1,0	1310	330	1634	7,5	2620	660	3268	14,0	2620	660	3268	14,0

120V AC

Model	1/8 Power PN															
	Idle				8 ohm				4 ohm				2 ohm			
	BTU/h	kCal/h	W line	A line	BTU/h	kCal/h	W line	A line	BTU/h	kCal/h	W line	A line	BTU/h	kCal/h	W line	A line
DALIM-5Q	290,03	73	85	0,7	706	178	817	7,2	706	178	817	7,2	706	178	817	7,2
DALIM-10Q	290,03	73	85	0,7	706	178	817	7,2	1412	356	1634	14,0	1412	356	1634	14,0
DALIM-14Q	382	96	112	1,0	1016	256	1176	10,3	1976	498	2288	19,2	1976	498	2288	19,2
DALIM-20Q	382	96	112	1,0	1412	356	1634	14,3	2823	712	3268	26,8	2823	712	3268	26,8