



Manufactured by C.E. Studio-2 s.l

Pol. Ind. La Figuera, C/ Rosa de Luxemburgo, nº34

46970 Alaquas, Valencia -SPAIN

Phone:+34 96 127 30 54

support@ramaudio.com

Current Draw and Thermal Dissipation RAM Audio Pi Series

230V AC

Model	Idle				1/8 Power PN											
					8 ohm				4 ohm				2 ohm			
	BTU/h	kCal/h	W line	A line	BTU/h	kCal/h	W line	A line	BTU/h	kCal/h	W line	A line	BTU/h	kCal/h	W line	A line
Pi2-3K	273,0	68,8	80,0	0,5	1958	493	849	5,6	2492	628	1080	7,1	2581	650	1119	7,4
Pi2-5K	273,0	68,8	80,0	0,5	2246	566	1058	7,0	2667	672	1257	8,3	3509	884	1653	10,9
Pi4-6K	273,0	68,8	80,0	0,5	3916	987	1698	11,2	5339	1346	2315	15,2	5161	1301	2238	14,7
Pi4-10K	273,0	68,8	80,0	0,5	2520	635	1538	10,1	5166	1302	2434	16,0	5166	1302	2434	16,0

120V AC

Model	Idle				1/8 Power PN											
					8 ohm				4 ohm				2 ohm			
	BTU/h	kCal/h	W line	A line	BTU/h	kCal/h	W line	A line	BTU/h	kCal/h	W line	A line	BTU/h	kCal/h	W line	A line
Pi2-3K	523,3	131,9	153	1,0	1958	493	1627	10,7	2492	628	2071	13,6	2581	650	2145	14,1
Pi2-5K	523,3	131,9	153	1,0	2246	566	2029	13,4	2667	672	2409	15,9	3509	884	3170	20,9
Pi 6K	523,3	131,9	153	1,0	3916	987	3254	21,4	5339	1346	4438	29,2	5161	1301	4290	28,3
Pi 10K	523,3	131,9	153	1,0	2520	635	2948	19,4	5166	1302	4666	30,7	5166	1302	4666	30,7