



**RAM** *Audio*®

# Third-Party Ethernet Control Manual

**Pi / DENEB / DALIM Series**

**API Version 1.1**

(Minimum firmware version v3.1)

## Index

INTRODUCTION .....	2
COMMUNICATION .....	2
DATA TYPE.....	2
1. Monitoring Parameters (UDP) .....	3
1.1. UDP Discovery Device Data.....	3
1.2. Real Time values monitor .....	5
1.3. Monitoring live data. Message to send.....	9
1.3.1. Enable / Disable Monitors .....	10
2. Control Commands (TCP) .....	11
2.1. General structure of data packets .....	11
2.1.1. Real-Time structure of data packets .....	12
2.1.1.1 Route Input Select.....	12
2.1.1.2 User Eq .....	13
2.1.1.3 User input gain.....	14
2.1.1.4 User output gain.....	15
2.1.1.5 User input delay .....	15
2.1.1.6 User output delay .....	16
2.1.1.7 Amplifier Volume Level .....	16
2.1.1.8 User HP Filter .....	17
2.1.2. Select Snapshot Preset.....	18
2.1.2.1 Select number of Snapshot .....	18
2.1.3. Set Device Name .....	19
2.1.3.1 Device Name.....	19
2.1.4. Select On/Off Standby .....	20
2.1.4.1 Select Standby.....	20
2.1.5. Get Device Basic Info.....	21
2.1.5.1 Header received when send “ <i>Get Device Basic Info</i> ” .....	21
2.1.5.2 <i>Data Received</i> .....	22
2.1.6. Select Get Third Part Info.....	23
2.1.6.1 Select Data .....	23
2.1.7. Header received when send “ <i>Get Third Part Info</i> ” .....	25
2.1.7.1 Data Received .....	25
2.1.8. Select Get Library List .....	28
2.1.9. Header received when send “ <i>Get Library List</i> ” .....	29
2.1.9.1 Data Received .....	29

## INTRODUCTION

The objective of this document is to be a guide to the “third-party” user when communicating with a RAM Audio amplifier via an Ethernet connection.

## COMMUNICATION

TCP is the protocol used for communicating a controller device with the amplifiers on an Ethernet network. Each amplifier is assigned a unique IP address on the local network where they will be installed.

All Ethernet-controllable amplifiers leave our factory configured to receive a dynamic IP through a DHCP server. If this server is not present, an auto IP will be assigned using the APIPA protocol. In any case, a manual IP can be configured.

In order to be able to communicate with any of these amplifiers, it is necessary to send the data to the IP mentioned above on the TCP port 1001. In the same way, all amplifiers will respond to the pre-selected IP control (selected by means of a command that will be later referred to).

On the other hand, the Controller must read the incoming TCP packet and extract the IP address that sends this data.

## DATA TYPE

In the communication between a RAM Audio amplifier and a controller, two types of data are found: the Monitoring Parameters (with which we can obtain the value of parameters like the output tension, the temperature, etc.) and the Control Commands (with which we can modify the value of certain amplifier parameters like the output level or its power-on state). This communication is made by means of data packets, the structure of which will be explained later.

# 1. Monitoring Parameters (UDP)

## 1.1. UDP Discovery Device Data

To obtain the device data we send an UDP frame with a single data value 0x58 ('X') to the IP: 255.255.255.255 and to port: 65535

The device will respond with an UDP frame with the following data.

Byte	Code	Description
0	0x41	Control value with the character 'A'
<i>The following bytes indicate the mac address of the device</i>		
1 ..	xx	Decimal value in ASCII code of the 6 digits of the mac <b>For a MAC FC:0F:E7:51:36:40 you receive: 32 35 32 2e 31 35 2e 32 33 31 2e 38 31 2e 35 34 2e 36 34 (252.15.231.81.54.64)</b>
..	0x2f	Data separation character '/'
<i>The following 4 data indicate the data receiving port of the device (1001)</i>		
..	0x31	'1'
..	0x30	'0'
..	0x30	'0'
..	0x31	'1'
..	0x2f	Data separation character '/'
<i>The next 5 bytes indicate the status of the device</i>		
..	0x4e	'N': Programing mode
..	0x2a	"": No errors
..	0x2a	"": Still to be implemented
..	xx	'M' : Static Mode 'I': DHCP Discovered "": DHCP Discovering 'Y': Static Mode 'Y': Auto-IP Mode
	xx	'C': Connected with other client "": Not connected
..	0x2f	Data separation character '/'
<i>The next bytes indicate the IP address</i>		
..	xx	Decimal value in ASCII code of the IP address <b>For a IP: 169.254.206.21 you receive: 31 36 39 2e 32 35 34 2e 32 30 36 2e 32 31 34</b>
..	0x2f	Data separation character '/'
<i>The next bytes indicate the hardware model</i>		
	xx	Characters in ASCII code <b>For "DSPBPi" you receive: 44 53 50 42 50 69</b>
..	0x2f	Data separation character '/'

Byte	Code	Description
<i>The next bytes indicate the device name</i>		
	xx	Characters in ASCII code

Byte	Code	Description
<b>For "NoName" you receive: 4e 6f 4e 61 6d 65</b>		
..	0x2f	Data separation character '/'
<i>The next bytes indicate the device model</i>		
..	xx	Characters in ASCII code <b>For "DALIM 14Q" you receive: 44 41 4c 49 4d 20 31 34 51</b>
..	0x2f	Data separation character '/'
<i>The next bytes indicate the brand name</i>		
..	xx	Characters in ASCII code <b>For "RAM Audio" you receive: 52 41 4d 20 41 75 64 69 6f</b>
..	0x2f	Data separation character '/'

## 1.2. Real Time values monitor

In parameter monitoring, different data are obtained continuously from the amplifier. This monitoring can be activated or deactivated at the user's request. This is a UDP communication.

### UDP receive header (when monitor communication is activated)

Byte	Code	Description
0	0x49	
1	0x50	
2	0x41	
3	0x44	
4	0x01	API Version
5	0x01	API Version
6	0x00	Message ID Size LSB (0x000000FF)
7	0x00	Message ID (0x0000FF00) » 8
8	0x00	Message ID (0x00FF0000) » 16
9	0x00	Message ID MSB (0xFF0000) » 24
10	0x09	Monitor
11	0x00	
12	0x73	Params Size LSB (0x000000FF)
13	0x00	Params Size MSB (0x0000FF00) » 8
14	0x00	
15	0x00	

Data is received in the following order.

Byte	Nº Bytes	Description
16	1	Device input channels
17	1	Device output channels
Input Vumeter		
18	2	Vumeter Correction (LSB Value: 0x00FF + MSB Value: 0xFF00)
20	2	CH1 vumeter value (LSB Value: 0x00FF + MSB Value: 0xFF00)
22	2	CH2 vumeter value (LSB Value: 0x00FF + MSB Value: 0xFF00)
24	2	CH3 vumeter value (LSB Value: 0x00FF + MSB Value: 0xFF00)
26	2	CH4 vumeter value (LSB Value: 0x00FF + MSB Value: 0xFF00)

Byte	Nº Bytes	Description
Output Vumeter		
28	2	Vumeter Correction (LSB Value: 0x00FF + MSB Value: 0xFF00)
30	2	CH1 vumeter before dynamics value (LSB Value: 0x00FF + MSB Value: 0xFF00)
32	2	CH1 vumeter after dynamics value (LSB Value: 0x00FF + MSB Value: 0xFF00)
34	2	CH2 vumeter before dynamics value (LSB Value: 0x00FF + MSB Value: 0xFF00)
36	2	CH2 vumeter after dynamics value (LSB Value: 0x00FF + MSB Value: 0xFF00)
38	2	CH3 vumeter before dynamics value (LSB Value: 0x00FF + MSB Value: 0xFF00)
40	2	CH3 vumeter after dynamics value (LSB Value: 0x00FF + MSB Value: 0xFF00)
42	2	CH4 vumeter before dynamics value (LSB Value: 0x00FF + MSB Value: 0xFF00)
44	2	CH4 vumeter after dynamics value (LSB Value: 0x00FF + MSB Value: 0xFF00)
*Analogue Levels (only DENEBO / DALIM)		
46	1	CH1 Volts sensor calibration Value
47	2	CH1 Volts Value (LSB Value: 0x00FF + MSB Value: 0xFF00)
49	1	CH2 Volts sensor calibration Value
50	2	CH2 Volts Value (LSB Value: 0x00FF + MSB Value: 0xFF00)
52	1	CH3 Volts sensor calibration Value
53	2	CH3 Volts Value (LSB Value: 0x00FF + MSB Value: 0xFF00)
55	1	CH4 Volts sensor calibration Value
56	2	CH4 Volts Value (LSB Value: 0x00FF + MSB Value: 0xFF00)
58	2	CH1 Current sensor calibration Value (LSB Value: 0x00FF + MSB Value: 0xFF00)
60	2	CH1 Current Value (LSB Value: 0x00FF + MSB Value: 0xFF00)
62	2	CH2 Current sensor calibration Value (LSB Value: 0x00FF + MSB Value: 0xFF00)
64	2	CH2 Current Value (LSB Value: 0x00FF + MSB Value: 0xFF00)
66	2	CH3 Current sensor calibration Value (LSB Value: 0x00FF + MSB Value: 0xFF00)
68	2	CH3 Current Value (LSB Value: 0x00FF + MSB Value: 0xFF00)
70	2	CH4 Current sensor calibration Value (LSB Value: 0x00FF + MSB Value: 0xFF00)
72	2	CH4 Current Value (LSB Value: 0x00FF + MSB Value: 0xFF00)
Byte	Nº Bytes	Description
Temperature		

<b>Byte</b>	<b>Nº Bytes</b>	<b>Description</b>
74	1	CH1 Temperature sensor calibration Value
75	2	CH1 Temperature Value (LSB Value: 0x00FF + MSB Value: 0xFF00)
77	1	CH2 Temperature sensor calibration Value
78	2	CH2 Temperature Value (LSB Value: 0x00FF + MSB Value: 0xFF00)
80	1	CH3 Temperature sensor calibration Value
81	2	CH3 Temperature Value (LSB Value: 0x00FF + MSB Value: 0xFF00)
83	1	CH4 Temperature sensor calibration Value
84	2	CH4 Temperature Value (LSB Value: 0x00FF + MSB Value: 0xFF00)
Clip (1: Enabled / 0: Disabled)		
86	1	CH1 Clip
87	1	CH2 Clip
88	1	CH3 Clip
89	1	CH4 Clip
Output Level Value		
90	4	CH1 Output Level (LSB Value: 0x00FF + MSB Value: 0xFF00 + Polarity + Mute)
94	4	CH2 Output Level (LSB Value: 0x00FF + MSB Value: 0xFF00 + Polarity + Mute)
98	4	CH3 Output Level (LSB Value: 0x00FF + MSB Value: 0xFF00 + Polarity + Mute)
102	4	CH4 Output Level (LSB Value: 0x00FF + MSB Value: 0xFF00 + Polarity + Mute)
**Fault State, 1 = correct operation (only DENEBO / DALIM)		
106	1	CH1 Fault State
107	1	CH2 Fault State
108	1	CH3 Fault State
109	1	CH4 Fault State
RMS Limit Threshold		
110	2	CH1 RMS Limit Threshold (LSB Value: 0x00FF + MSB Value: 0xFF00)
112	2	CH2 RMS Limit Threshold (LSB Value: 0x00FF + MSB Value: 0xFF00)
114	2	CH3 RMS Limit Threshold (LSB Value: 0x00FF + MSB Value: 0xFF00)
116	2	CH4 RMS Limit Threshold (LSB Value: 0x00FF + MSB Value: 0xFF00)
PEAK Limit Threshold		
118	2	CH1 PEAK Limit Threshold (LSB Value: 0x00FF + MSB Value: 0xFF00)
120	2	CH2 PEAK Limit Threshold (LSB Value: 0x00FF + MSB Value: 0xFF00)
122	2	CH3 PEAK Limit Threshold (LSB Value: 0x00FF + MSB Value: 0xFF00)

Byte	Nº Bytes	Description
124	2	CH4 PEAK Limit Threshold (LSB Value: 0x00FF + MSB Value: 0xFF00)
***GPI MUTE Value (only DENEB / DALIM)		
126	1	GPI MUTE Value
Priority Active		
127	1	CH1 Priority Active
128	1	CH2 Priority Active
129	1	CH3 Priority Active
130	1	CH4 Priority Active

\*In Pi amplifiers this value corresponds to the DSP output level after dynamics

\*\*Pi amps do not have this sensor. The value will always be 1

\*\*\*Pi amps do not have this feature. The value will always be 0

### 1.3. Monitoring live data. Message to send

#### Header

Byte	Code	Description
0	0x53	
1	0x43	
2	0x4f	
3	0x4c	
4	0x01	API Version
5	0x01	API Version
6	0x00	Message ID Size LSB (0x000000FF)
7	0x00	Message ID (0x0000FF00) » 8
8	0x00	Message ID (0x00FF0000) » 16
9	0x00	Message ID MSB (0xFF0000) » 24
10	0x09	<b>Monitor</b>
11	0x00	
12	0x0e	Params Size LSB (0x000000FF)
13	0x00	Params Size MSB (0x0000FF00) » 8
14	0x00	
15	0x00	

### 1.3.1. Enable / Disable Monitors

This is a 13 bytes data and includes the activated monitoring selection, received Port, received IP and received MAC.

RT Header (16 Bytes)		Data (13 Bytes)
<hr/>		

Byte	Code	Description
0	0x00 0x01	Monitor Disabled Monitor Enabled
1	0x03	Monitor Port (MSB: 0xFF00)
2	0xea	Monitor Port (LSB: 0x00FF)
3	0xa9	Monitor Target IP
4	0xfe	Monitor Target IP
5	0x17	Monitor Target IP
6	0xb0	Monitor Target IP
7	0x00	Monitor Target MAC
8	0x01	Monitor Target MAC
9	0x02	Monitor Target MAC
10	0x03	Monitor Target MAC
11	0x04	Monitor Target MAC
12	0x05	Monitor Target MAC
13	0x00	--

Example:

To activate receive monitors in Port:1002 in device with IP: 192.168.23.11, MAC: 00:01:02:03:04:05

**53 43 4f 4c 01 01 28 00 00 00 09 00 0d 00 00 00 01 03 ea a9 fe 17 0b 00 01 02 03 04 05 00**

## 2. Control Commands (TCP)

### 2.1. General structure of data packets

The data packets consist of a series of bytes and their length will vary according to each case. In this manual, the bytes are represented in different ways, either in hexadecimal or decimal format.

**Real-Time control message header**

Byte	Code	Description
0	0x53	
1	0x43	
2	0x4f	
3	0x4c	
4	0x01	API Version
5	0x01	API Version
6	0x00	Message ID Size LSB (0x000000FF)
7	0x00	Message ID (0x0000FF00) » 8
8	0x00	Message ID (0x00FF0000) » 16
9	0x00	Message ID MSB (0xFF0000) » 24
10	0XXX	<b>Command</b>
11	0x00	
12	0x0a	Params Size LSB (0x000000FF)
13	0x00	Params Size MSB (0x0000FF00) » 8
14	0x00	
15	0x00	

Byte 10 determines **Command** requested from the device.

Requested commands can be the following:

Command	Hex Value
Real Time	0x08
Monitor	0x09
Set Device Name	0x0C
Get Library List	0x0F
Set Power Status	0x10
Recall Snapshot Preset	0x20
Get Device Basic Info	0x23
Get Third Part Info	0xC8

## 2.1.1. Real-Time structure of data packets

### Real-Time control message header

Byte	Code	Description
0	0x53	
1	0x43	
2	0x4f	
3	0x4c	
4	0x01	API Version
5	0x01	API Version
6	0x00	Message ID Size LSB (0x000000FF)
7	0x00	Message ID (0x0000FF00) » 8
8	0x00	Message ID (0x00FF0000) » 16
9	0x00	Message ID MSB (0xFF0000) » 24
10	0x08	<b>Real Time Command</b>
11	0x00	
12	0x0a	Params Size LSB (0x000000FF)
13	0x00	Params Size MSB (0x0000FF00) » 8
14	0x00	
15	0x00	

Within the real-time instructions, in byte 16, it is determined which device value we want to change

Byte 16 Hex Value	Value to change
0x03	User Eq
0x1F	User Gain
0x20	User Delay
0x21	Amplifier Volume Level
0x27	User HP
0x28	Route Input Select

### 2.1.1.1 Route Input Select

It is a 7 bytes data and includes the selection of input routing and its value.

RT Header (16 Bytes)	Data (7 Bytes)
----------------------	----------------

Byte	Code	Description
0	0x28	Route Input Select
1	xx	(The same as byte 5)
2	0x00	Matrix Type (Always 0)

3	0x01	Always this value
4	0x04	Always this value
5	0x01 0x02 0x03 0x04	Route CH A Route CH B Route CH C Route CH D
6	0x00 0x01 0x02 0x03 0x04 0x05 0x06	Select Input 1 Select Input 2 Select Input 3 Select Input 4 Select Input 1+2 Select Input 3+4 Select Matrix
7	0xff	Always this value

Example:

To select input 1+2 in route C, send:

**53 43 4f 4c 01 01 28 00 00 00 08 00 07 00 00 00 28 03 00 01 04 03 04 ff**

### 2.1.1.2 User Eq

This data is 10 bytes long.

RT Header (16 Bytes)		Data (6 Bytes)
Byte	Code	Description
0	0x03	User Eq
1	0x01 0x02 0x03 0x04	Input 1 Input 2 Input 3 Input 4
2	0x13 0x14 0x15 0x16 0x17 0x18	EQ Band 1 EQ Band 2 EQ Band 3 EQ Band 4 EQ Band 5 EQ Band 6
3	xx	Filter Type (See table below)*
4	xx	Frequency. Lower part of the word (0x00FF)
5	xx	Frequency. Upper part of the word (0xFF00).
6	xx	Gain (value x10). Lower part of the word (0x00FF)
7	xx	Gain (value x10). Upper part of the word (0xFF00).
8	xx	Q (value x10)
9	0x00 0x01	Disable Band Enable Band
10	0x00 0x01	Disable Main Eq Enable Main Eq

Index	Filter Type Description
0x00	Bypass
0x01	Parametric with adapted Q
0x02	Parametric with constant Q
0x03	Low-pass shelving filter 6 dB's
0x04	High-pass shelving filter 6 dB's
0x05	Low-pass shelving filter 12 dB's
0x06	High-pass shelving filter 12 dB's
0x07	Low-pass shelving filter 12 dB's with Q
0x08	High-pass shelving filter 12 dB's with Q
0x09	Low-pass
0x0a	High-pass
0x0b	Low-pass with Q
0x0c	High-pass with Q
0x0d	Band pass
0x0e	Remove band
0x0f	Bypass with 180° offset
0x10	Bypass with 360° offset

Example:

To put in channel 1 input gain of +12dB with normal polarity and unmuted, send:

**53 43 4f 4c 01 01 01 00 00 08 00 0a 00 00 00 1f 01 78 00 00 01+**

### 2.1.1.3 *User input gain*

This data is 6 bytes long and includes gain, mute and polarity control.

RT Header (16 Bytes)		Data (6 Bytes)
Byte	Code	Description
0	0x1f	User gain
1	0x01 0x02 0x03 0x04	Input Way 1 Input Way 2 Input Way 3 Input Way 4
2	xx	Gain in dB. Lower part of the word (0x00FF). +12.0 to -40.0 dB
3	xx	Gain in dB. Upper part of the word (0xFF00). +12.0 to -40.0 dB
4	0x00 0x01	Normal polarity Inverted polarity
5	0x00 0x01	Muted Unmuted

Example:

To put in channel 1 input gain of +12dB with normal polarity and unmuted, send:

**53 43 4f 4c 01 01 01 00 00 08 00 0a 00 00 00 1f 01 78 00 00 01**

### 2.1.1.4 User output gain

This data is 6 bytes long and includes gain, mute and polarity control.

RT Header (16 Bytes)		Data (6 Bytes)
Byte	Code	Description
0	0x1f	User gain
1	0x10 0x20 0x30 0x40	Output Way 1 Output Way 2 Output Way 3 Output Way 4
2	xx	Gain in dB. Lower part of the word (0x00FF). +120 to -400 (Real value +12.0 to -40.0 dB)
3	xx	Gain in dB. Upper part of the word (0xFF00). +120 to -400 (Real value +12.0 to -40.0 dB)
4	0x00 0x01	Normal polarity Inverted polarity
5	0x00 0x01	Muted Unmuted

Example:

To put in channel 1 output gain of +12dB with normal polarity and unmuted, type:

**53 43 4f 4c 01 01 01 00 00 00 08 00 0a 00 00 00 1f 10 78 00 00 01**

### 2.1.1.5 User input delay

This data is 4 bytes long. For channel 1 maximum value is 300.0 ms., for the rest 90.0 ms.

RT Header (16 Bytes)		Data (6 Bytes)
Byte	Code	Description
0	0x20	User Delay
1	0x01 0x02 0x03 0x04	Input Way 1 Input Way 2 Input Way 3 Input Way 4
2	xx	Delay value x10. Lower part of the word (0x00FF).
3	xx	Delay value x10. Upper part of the word (0xFF00).

Example:

To put in channel 1 input delay 12.6 ms., send:

**53 43 4f 4c 01 01 01 00 00 00 08 00 03 00 00 00 20 01 7E 00**

### 2.1.1.6 User output delay

This data is 4 bytes long. The maximum value is 90.0 ms.

RT Header (16 Bytes)		Data (6 Bytes)
Byte	Code	Description
0	0x20	User Delay
1	0x10 0x20 0x30 0x40	Output Way 1 Output Way 2 Output Way 3 Output Way 4
2	xx	Delay value x10. Lower part of the word (0x00FF).
3	xx	Delay value x10. Upper part of the word (0xFF00).

Example:

To put in channel 1 output delay 12,6 ms., send:

**53 43 4f 4c 01 01 01 00 00 00 08 00 03 00 00 00 20 10 7E 00**

### 2.1.1.7 Amplifier Volume Level

This data is 6 bytes long and includes gain, mute and polarity control.

RT Header (16 Bytes)		Data (6 Bytes)
Byte	Code	Description
0	0x21	Amplifier Volume Level
1	0x10 0x20 0x30 0x40	Output Way 1 Output Way 2 Output Way 3 Output Way 4
2	xx	Gain in dB. Lower part of the word (0x00FF). +120 to -400 (Real value +12.0 to -40.0 dB)
3	xx	Gain in dB. Upper part of the word (0xFF00). +120 to -400 (Real value +12.0 to -40.0 dB)
4	0x00 0x01	Normal polarity Inverted polarity
5	0x00 0x01	Muted Unmuted

Example:

To put in channel 1 level volume gain of +12dB with normal polarity and unmuted, type:

**53 43 4f 4c 01 01 01 00 00 00 08 00 0a 00 00 00 21 10 78 00 00 01**

### 2.1.1.8 User HP Filter

This data is 8 bytes long and includes gain, filter type, frequency cut, order and active control.

RT Header (16 Bytes)		Data (8 Bytes)
Byte	Code	Description
0	0x27	HP user filter gain
1	0x01 0x02 0x03 0x04	Input Way 1 Input Way 2 Input Way 3 Input Way 4
2	0x00	0: High Pass
3	0x00 0x01 0x02	Xover Type: Butterworth Linkwitz-Riley Bessel
4	xx	Frequency Cut [20..20000] LSB (0x00FF)
5	xx	Frequency Cut [20..20000] MSB (0xFF00)»8
6	0x00..0x08	Order
7	0x00 0x01	Active Disabled Active Enabled

Example:

To activate the user HP Butterworth filter on channel 1 at a cut-off frequency of 50 Hz with order 4, send:

53 43 4f 4c 01 01 01 00 00 00 08 00 0a 00 00 00 **27 01 00 00 32 00 04 01**

## 2.1.2. Select Snapshot Preset

### Select Snapshot Preset message header

Byte	Code	Description
0	0x53	
1	0x43	
2	0x4f	
3	0x4c	
4	0x01	API Version
5	0x01	API Version
6	0x00	Message ID Size LSB (0x000000FF)
7	0x00	Message ID (0x0000FF00) » 8
8	0x00	Message ID (0x00FF0000) » 16
9	0x00	Message ID MSB (0xFF0000) » 24
10	0x20	<b>Snapshot Recall</b>
11	0x00	
12	0x0a	Params Size LSB (0x000000FF)
13	0x00	Params Size MSB (0x0000FF00) » 8
14	0x00	
15	0x00	

### 2.1.2.1     *Select number of Snapshot*

This data is 1 byte long and includes the number of Snapshot to select.

Snapshot Select Header (16 Bytes)		Data (1 Bytes)
Byte	Code	Description
0	xx	Snapshot preset number (1..20)

Example:

To select the Snapshot number 2, send:

53 43 4f 4c 01 01 00 00 00 00 20 00 01 00 00 00 **02**

### 2.1.3. Set Device Name

#### Select Snapshot Preset message header

Byte	Code	Description
0	0x53	
1	0x43	
2	0x4f	
3	0x4c	
4	0x01	API Version
5	0x01	API Version
6	0x00	Message ID Size LSB (0x000000FF)
7	0x00	Message ID (0x0000FF00) » 8
8	0x00	Message ID (0x00FF0000) » 16
9	0x00	Message ID MSB (0xFF0000) » 24
10	0xC0	<b>Set Device Name</b>
11	0x00	
12	0x0e	Params Size LSB (0x000000FF)
13	0x00	Params Size MSB (0x0000FF00) » 8
14	0x00	
15	0x00	

#### 2.1.3.1 Device Name

The device name has a maximum length of 14 characters. Each character corresponds to the ASCII code

Snapshot Select Header (16 Bytes)		Data (1 Bytes)
Byte	Code	Description
0..14	xx	Device Name in ASCII code

Example:

To change the device name to “Amp2”, send:

53 43 4f 4c 01 01 00 00 00 00 0C 00 0E 00 00 00 **41 6D 70 32**

## 2.1.4. Select On/Off Standby

### Select Snapshot Preset message header

Byte	Code	Description
0	0x53	
1	0x43	
2	0x4f	
3	0x4c	
4	0x01	API Version
5	0x01	API Version
6	0x00	Message ID Size LSB (0x000000FF)
7	0x00	Message ID (0x0000FF00) » 8
8	0x00	Message ID (0x00FF0000) » 16
9	0x00	Message ID MSB (0xFF0000) » 24
10	0x10	<b>Standby</b>
11	0x00	
12	0x01	Params Size LSB (0x000000FF)
13	0x00	Params Size MSB (0x0000FF00) » 8
14	0x00	
15	0x00	

### 2.1.4.1 Select Standby

This data is 1 byte long and includes the number of Snapshot to select.

Snapshot Select Header (16 Bytes)		Data (1 Bytes)
Byte	Code	Description
0	0x00 0x01	Standby Enabled Standby Disabled

Example:

To put the device in Standby, send:

**53 43 4f 4c 01 01 00 00 00 00 10 00 01 00 00 00 00**

## 2.1.5. Get Device Basic Info

Select Snapshot Preset message header

Byte	Code	Description
0	0x53	
1	0x43	
2	0x4f	
3	0x4c	
4	0x01	API Version
5	0x01	API Version
6	0x00	Message ID Size LSB (0x000000FF)
7	0x00	Message ID (0x0000FF00) » 8
8	0x00	Message ID (0x00FF0000) » 16
9	0x00	Message ID MSB (0xFF0000) » 24
10	0x23	<b>Get Device Basic Info</b>
11	0x00	
12	0x01	Params Size LSB (0x000000FF)
13	0x00	Params Size MSB (0x0000FF00) » 8
14	0x00	
15	0x00	

Example:

To get the device basic info, send:

53 43 4f 4c 01 01 00 00 00 00 23 00 01 00 00 00 00

### 2.1.5.1 Header received when send “Get Device Basic Info”

Byte	Code	Description
0	0x49	
1	0x50	
2	0x41	
3	0x44	
4	0x01	API Version
5	0x01	API Version
6	0x00	Message ID Size LSB (0x000000FF)
7	0x00	Message ID (0x0000FF00) » 8
8	0x00	Message ID (0x00FF0000) » 16
9	0x00	Message ID MSB (0xFF0000) » 24
10	0x23	<b>Get Device Basic Info</b>
11	0x00	
12	0xa0	Params Size LSB (0x000000FF)

13	0x00	Params Size MSB (0x0000FF00) » 8
14	0x00	
15	0x00	

### 2.1.5.2 Data Received

Byte	Code	Description
16	xx	Hardware type
17	xx	Module hardware version
18..33	xx	Serial Number
34..53	xx	Manufacturer name
54..73	xx	Model name
74	0x00 0x01	without AES3 with AES3
75	0x00 0x01	without DANTE / AES67 with DANTE / AES67
76	0x00 0x01	without Voltage sensor with Voltage sensor
77	0x00 0x01	without Impedance sensor with Impedance sensor
78	0x00 0x01	without temperature sensor with temperature sensor
79	0x00 0x01	without standby with standby
80	0x00 0x01	2 channels output 4 channels output

Byte	Code	Description
81	xx	Operation Time in hours. Lower part of the word (0x00FF). +120 to -400 (Real value +12.0 to -40.0 dB)
82	xx	Operation Time in hours. Upper part of the word (0xFF00). +120 to -400 (Real value +12.0 to -40.0 dB)
83	xx	Operation Time in 15 minutes block
84	0x00 0x01	without GPIO with GPIO

## 2.1.6. Select Get Third Part Info

### Select Get Device Data message header

Byte	Code	Description
0	0x53	
1	0x43	
2	0x4f	
3	0x4c	
4	0x01	API Version
5	0x01	API Version
6	0x00	Message ID Size LSB (0x000000FF)
7	0x00	Message ID (0x0000FF00) » 8
8	0x00	Message ID (0x00FF0000) » 16
9	0x00	Message ID MSB (0xFF0000) » 24
10	0xC8	<b>Get Third Part Info</b>
11	0x00	
12	0x0a	Params Size LSB (0x000000FF)
13	0x00	Params Size MSB (0x0000FF00) » 8
14	0x00	
15	0x00	

### 2.1.6.1 Select Data

This data is 2 bytes long and includes the selected data and the channel to get information.

Get Device Data Header (16 Bytes)	Data (2 Bytes)
-----------------------------------	----------------

Byte	Code	Description
16	0x00 0x01 0x02 0x03 0x04 0x05 0x06 0x09 0x0A 0x0B 0x0C	Preset Name Use Name Way Name Snapshot Name Device Name User Input Gain User Output Gain Get Volume Get Join Select Get User Eq Get User Delay
17	0x01 0x02 0x03 0x04	Channel 1 Channel 2 Channel 3 Channel 4

Example:

To get the input data gain from channel 2, send:

**53 43 4f 4c 01 01 00 00 00 00 **C8 00 01 00 00 00 05 01****

## 2.1.7. Header received when send “Get Third Part Info”

Byte	Code	Description
0	0x49	
1	0x50	
2	0x41	
3	0x44	
4	0x01	API Version
5	0x01	API Version
6	0x00	Message ID Size LSB (0x000000FF)
7	0x00	Message ID (0x0000FF00) » 8
8	0x00	Message ID (0x00FF0000) » 16
9	0x00	Message ID MSB (0xFF0000) » 24
10	0xC8	<b>Get Third Part Info</b>
11	0x00	
12	0x0a	Params Size LSB (0x000000FF)
13	0x00	Params Size MSB (0x0000FF00) » 8
14	0x00	
15	0x00	

\*If the communications header received by the amplifier is not correct, the amplifier will return a response header with byte 11 with value 0x01

### 2.1.7.1 Data Received

This data is of variable length and depends on the information requested

Received message Header (16 Bytes)	Data (variable length)
------------------------------------	------------------------

#### Preset Name

Byte	Code	Description
16...27	xx	Character in Hex ASCII code

#### Use Name

Byte	Code	Description
16...27	xx	Character in Hex ASCII code

#### Way Name

Byte	Code	Description
16...21	xx	Character in Hex ASCII code

**Snapshot Name**

<b>Byte</b>	<b>Code</b>	<b>Description</b>
16...37	xx	Character in Hex ASCII code

**Device Name**

<b>Byte</b>	<b>Code</b>	<b>Description</b>
16...23	xx	Character in Hex ASCII code

**User Input Gain Data**

<b>Byte</b>	<b>Code</b>	<b>Description</b>
16	xx	Gain in dB. Lower part of the word (0x00FF). +120 to -400 (Real value +12.0 to -40.0 dB)
17	xx	Gain in dB. Upper part of the word (0xFF00). +120 to -400 (Real value +12.0 to -40.0 dB)
18	0x00 0x01	Normal polarity Inverted polarity
19	0x00 0x01	Muted Unmuted

**User Output Gain Data**

<b>Byte</b>	<b>Code</b>	<b>Description</b>
16	xx	Gain in dB. Lower part of the word (0x00FF). +120 to -400 (Real value +12.0 to -40.0 dB)
17	xx	Gain in dB. Upper part of the word (0xFF00). +120 to -400 (Real value +12.0 to -40.0 dB)
18	0x00 0x01	Normal polarity Inverted polarity
19	0x00 0x01	Muted Unmuted

**Get Volume**

<b>Byte</b>	<b>Code</b>	<b>Description</b>
16	xx	Gain in dB. Lower part of the word (0x00FF). +120 to -400 (Real value +12.0 to -40.0 dB)
17	xx	Gain in dB. Upper part of the word (0xFF00). +120 to -400 (Real value +12.0 to -40.0 dB)
18	0x00 0x01	Normal polarity Inverted polarity
19	0x00 0x01	Muted Unmuted

**Get Join Select**

<b>Byte</b>	<b>Code</b>	<b>Description</b>
16	0x00 0x01	Disable Join Enable Join

## Get User Eq

Byte	Code	Description
16	0x00 0x01	Main Eq disable Main Eq Enable
<i>The equalizer has 6 equalization bands that are received sequentially starting with 1 and ending with 6. The data follows the next order and repeats sequentially for a full channel.</i>		
..	xx	Type (see table in page 13)
..	xx	Frequency. Lower part of the word (0x00FF).
..	xx	Frequency. Upper part of the word (0xFF00).
..	xx	Gain (x10). Lower part of the word (0x00FF).
..	xx	Gain (x10). Upper part of the word (0xFF00).
..	xx	Q value (x10)
..	0x00 0x01	Eq Band Disable Eq Band Enable

*The frame, without the header, has a total length of 43 bytes*

## Get User Delay

Byte	Code	Description
16	xx	Delay (x10). Lower part of the word (0x00FF).
17	xx	Delay (x10). Upper part of the word (0xFF00).

Example:

If you send input data gain from channel 2:

53 43 4f 4c 01 01 00 00 00 00 **C8** 00 01 00 00 00 **05 01**

You receive, if Gain = +7 dB, Normal polarity and Unmuted:

49 50 41 44 01 01 00 00 00 00 **C8** 00 **04** 00 00 00 **46 00 01 01**

## 2.1.8. Select Get Library List

### Select Get Device Data message header

Byte	Code	Description
0	0x53	
1	0x43	
2	0x4f	
3	0x4c	
4	0x01	API Version
5	0x01	API Version
6	0x00	Message ID Size LSB (0x000000FF)
7	0x00	Message ID (0x0000FF00) » 8
8	0x00	Message ID (0x00FF0000) » 16
9	0x00	Message ID MSB (0xFF0000) » 24
10	0x0F	<b>Get Library List</b>
11	0x00	
12	0x0a	Params Size LSB (0x000000FF)
13	0x00	Params Size MSB (0x0000FF00) » 8
14	0x00	
15	0x00	

Example:

To get the different name presets, send:

**53 43 4f 4c 01 01 00 00 00 00 0F 00 01 00 00 00 00**

## 2.1.9. Header received when send “*Get Library List*”

In a first data transmission, the received header indicates the number of data that are going to be received (Params size)

Byte	Code	Description
0	0x49	
1	0x50	
2	0x41	
3	0x44	
4	0x01	API Version
5	0x01	API Version
6	0x00	Message ID Size LSB (0x000000FF)
7	0x00	Message ID (0x0000FF00) » 8
8	0x00	Message ID (0x00FF0000) » 16
9	0x00	Message ID MSB (0xFF000000) » 24
10	0x0F	<b>Get Library List</b>
11	0x00	
12	0x0a	Params Size LSB (0x000000FF)
13	0x00	Params Size MSB (0x0000FF00) » 8
14	0x00	
15	0x00	

In the following communications the names of the different presets are sent.

### 2.1.9.1 Data Received

You will receive a frame with the following characteristics

Byte	Data	Description
16	'S'	Indicates that the name of a snapshot has to be received
17	xx	Number of snapshot
18...	xx	Name of Snapshot
..	'\0'	At the end of the text a null character will be received

This data structure continues until all the names of the snapshots present on the amplifier are complete.

When a first data with the character 'P' is received, it will indicate that the next name is that of an amplifier system preset. The same data reception structure will continue as for Snapshots.

Byte	Data	Description
..	'P'	Indicates that the name of a snapshot is to be received
..	xx	Number of snapshot
..	xx	Name of Snapshot
..	'\0'	At the end of the text a null character will be received

If you receive the following data frame:

**49 50 41 44 01 01 00 00 00 0F 00 04 00 00 00 53 01 44 69 72 65 63 74 20 4f 75 74 00 53  
02 42 61 73 69 63 20 4d 6f 6e 6f 20 28 31 20 69 6e 20 34 29 00**

You receive names of Snapshots

1. ***“Direct Out”***
2. ***“Basic Mono (1 in 4)”*** If you receive the following data frame:

**49 50 41 44 01 01 00 00 00 0F 00 04 00 00 00 53 01 44 69 72 65 63 74 20 4f 75 74 00 53  
02 42 61 73 69 63 20 4d 6f 6e 6f 20 28 31 20 69 6e 20 34 29 00**

You receive names of Snapshots

1. ***“Direct Out”***
2. ***“Basic Mono (1 in 4)”***



**Manufactured in the EU by C.E. Studio-2 s.l.  
Pol. Ind. La Figuera - C/ Rosa Luxemburgo nº34  
46970 Alaquas - Valencia - SPAIN  
Phone: +34 96 127 30 54 Fax: +34 96 127 30 56  
ramaudio.com, info@ramaudio.com**